

# WEBBING

## FALL RESTRAINT



**High performance fall protection,  
for those performing up high.**

### Product Features

- 100% Made in the USA
- One -Piece Shock  
Absorbing Lanyard
- Patent Pending
- Meets OSHA Standards
- "Remove From Service"  
Indicator

# Insist on only genuine TapeCraft® high performance webbing, made to stand up to whatever the task may be.

## Specifications for High Performance TapeCraft Load Limiter

- One-piece shock-absorbing lanyard featuring energy-absorbing member (POY) and strength member (outer tube) woven as one.
- Patent pending
- Saves tedious and expensive assembly process
- Arresting force limited to 700-800 lbf as the webbing expands
- At full expansion of +/-40", strength member is engaged and stops the fall
- Tensile strength >6000 lbf
- Passes OSHA standard drop test (fall distance=6', weight=220 lbs, max arresting force <900 lbf stopping distance <42")
- "Remove from Service" indicator woven into webbing



## A Complete Line of Webbing for Fall Restraint

**A0025:** 6 ft Standard POY Lanyard (Nylon)

**A0033:** 4 ft Standard POY Lanyard (Nylon)

**A0034:** 4 ft Standard POY Lanyard (Polyester)

**A0035:** 6 ft Standard POY Lanyard (Polyester)

**A0036:** Twin Leg 6 ft POY Lanyard (Polyester)

**A0040:** 6 ft Universal Lanyard (Polyester)

**U0111-1¾":** Grommet Webbing (Polyester)

**U0114-1¾":** 6,000 lb Harness Webbing (Polyester)

**U0115-1¾":** 12,000 lb Lanyard (Polyester)

**U0117-1":** 9,800 lb Lanyard (Polyester)

**E700:** Elastic Keeper